

Pinpoint a potential radioactive source quickly and safely with a RC22 or RC23 Wand.

- Fully automatic and easy to use
- Light weight
- Extendible for longer reach
- Easy to read backlit display
- Quick response time with variable alarm tone



RC22 & 23 WAND

TELESCOPIC RADIATION DETECTOR

Fully Automatic and Operator Friendly

The RC22 and RC23 were designed to allow fast and easy inspection of areas, containers or vehicles that may contain radioactive material. Upon start up the unit will perform a background check and automatically set an alarm threshold for the user. In only seconds the RC22 and RC23 is ready for use.

Easy to Read Display with Audible Alarm

When radiation is detected the display will immediately show the increasing radiation levels. An audio alarm will also be activated to help locate the exact source of the radiation. The tone varies based upon the proximity and intensity of the radioactive source.

Available In Two Lengths and Two Head Sizes

RC22 is telescopic for a reach of 49" (124.5cm) to 99" (251.5cm). The telescopic pole serves two functions, one is to reach and scan an area that would normally be out of reach, and the second is to provide a safer operating distance between you and a potential radioactive source.

The Wand is available in two different detector head sizes. The RC22 has a detector head size of 2" (5.1cm) for a total volume of 193cc. For greater sensitivity, the RC23 has a detector head size of 3" (7.6cm) for a total volume of 442cc.



RC22 & 23 Specifications:

Display:

- Large 2.17" (55mm) x 2.17" (55mm) backlit display LCD display.
- Display radiation level in selected unit of measurement, battery life, background level, and alarm threshold

Operation:

- Single button activation automatically sets audio alarm threshold level and displays unit of measurements (CPS, nSv/h, uR/h)

Energy Response Range:

- From 30Kev – 3.0Mev

Temperature Range:

- -10°C to +50°C (+14°F to +122°F)

Battery:

- 2 sets of NiMH 10,000 mA/h rechargeable or 2 x size "D" cell batteries

Each RC22 and RC23 Package Includes:

- RC22 or RC23 fully charged and ready for use
- Carrying Case
- Rubber tip boot cover (Quantity 2)
- Earphone
- Universal battery charger
- Operation manual



Size:

Model	Head Size	Extendible Length	Weight	Detector Size
RC22 Short	2" (5.1cm)	49" (124.5cm) to 68" (172.7cm)	5.2 lbs (2.36 kg)	193 cc
RC22 Long	2" (5.1cm)	68" (172.7cm) to 99" (251.5cm)	5.4 lbs (2.72 kg)	193 cc
RC23	3" (7.6cm)	49" (124.5cm) to 68" (172.7cm)	6.0 lbs (2.45 kg)	442 cc

CORPORATE HEADQUARTERS

Rock Branch Industrial Park
 303 Jacobson Drive
 Poca, West Virginia 25159
304.755.8321
800.955.8321

Kanawha
 Scales & Systems

KSS BRANCH OFFICES

Birmingham, AL888.313.6262
 Montgomery, AL334.281.5803
 Pikeville, KY888.703.8171
 Detroit, MI800.252.9712
 Flint, MI888.791.2351
 Cincinnati, OH888.280.7254
 Columbus, OH800.231.1679

Dayton, OH800.387.7297
 Pittsburgh, PA800.874.0591
 St. Mary's, PA800.874.0591
 Memphis, TN901.375.4877
 Parkersburg, WV800.926.0174
 Fairmont, WV800.872.0337

Visit us online at www.kanawhascales.com